



High Performance Network Security

PRODUCT MATRIX



SEPTEMBER 2014



FortiGate Network Security Platform - *Top Selling Models Matrix

| | FG/FWF-30D | FG/FWF-60C | FG/FWF-60D | FG-80D | FG-70D, FG/FWF-90D | FG-100D | FG-200D | FG-300D | FG-500D | FG-600C |
|--|--|--|----------------------------|---|--|--|--|--------------------------------------|--------------------------------------|--|
| Firewall Throughput (1518/512/64 byte UDP) | 0.8 / 0.8 / 0.8 Gbps | 1 / 1 / 1 Gbps | 1.5 / 1.5 / 1.5 Gbps | 1.3 / 0.95 / 0.17 Gbps | 3.5 / 3.5 / 3.5 Gbps | 2.5 / 1 / 0.2 Gbps | 3 / 3 / 3 Gbps | 8 / 8 / 8 Gbps | 16 / 16 / 16 Gbps | 16 / 16 / 16 Gbps |
| Firewall Latency | 8 µs | 4 µs | 4 µs | 90 µs | 4 µs | 37 µs | 2 µs | 3 µs | 3 µs | 7 µs |
| Concurrent Sessions | 200,000 | 400,000 | 500,000 | 1.5 Mil | 2 Mil | 3 Mil | 3.2 Mil | 6 Mil | 6 Mil | 3 Mil |
| New Sessions/Sec | 3,500 | 3,000 | 4,000 | 22,000 | 4,000 | 22,000 | 77,000 | 200,000 | 280,000 | 70,000 |
| Firewall Policies | 5,000 | 5,000 | 5,000 | 5,000 | 5,000 | 10,000 | 10,000 | 10,000 | 10,000 | 10,000 |
| IPSec VPN Throughput | 350 Mbps | 70 Mbps | 1 Gbps | 200 Mbps | 1 Gbps | 450 Mbps | 1.3 Gbps | 7 Gbps | 14 Gbps | 8 Gbps |
| Max G/W to G/W IPSEC Tunnels | 20 | 50 | 200 | 200 | 200 | 2,000 | 2,000 | 2,000 | 2,000 | 2,000 |
| Max Client to G/W IPSEC Tunnels | 250 | 500 | 500 | 1,000 | 1,000 | 5,000 | 5,000 | 10,000 | 10,000 | 50,000 |
| SSL VPN Throughput | 25 Mbps | 19 Mbps | 30 Mbps | 130 Mbps | 35 Mbps | 300 Mbps | 400 Mbps | 350 Mbps | 400 Mbps | 1 Gbps |
| Recommended SSL VPN Users | 80 | 100 | 100 | 200 | 200 | 300 | 300 | 500 | 500 | 5,000 |
| IPS Throughput | 150 Mbps | 135 Mbps | 200 Mbps | 800 Mbps | 275 Mbps | 950 Mbps | 1.7 Gbps | 2.8 Gbps | 4.7 Gbps | 4 Gbps |
| Antivirus Throughput (Proxy-Based/ Flow-Based) | 30 / 40 Mbps | 20 / 40 Mbps | 35 / 50 Mbps | 250 / 550 Mbps | 35 / 65 Mbps | 300 / 700 Mbps | 600 / 1,100 Mbps | 1.4 / 2.5 Gbps | 1.7 / 3.4 Gbps | 1.3 / 2.8 Gbps |
| Max FortiAPs (Total / Tunnel) | 2 / 2 | 10 / 5 | 10 / 5 | 32 / 16 | 32 / 16 | 64 / 32 | 128 / 64 | 512 / 256 | 512 / 256 | 1024 / 512 |
| Max FortiTokens | 20 | 100 | 100 | 100 | 100 | 1,000 | 1,000 | 1,000 | 1,000 | 1,000 |
| Max Registered FortiClient | 200 | 200 | 200 | 200 | 200 | 600 | 600 | 600 | 2,000 | 2,000 |
| Virtual Domains (Default/Max) | - | 10 / 10 | 10 / 10 | 10 / 10 | 10 / 10 | 10 / 10 | 10 / 10 | 10 / 10 | 10 / 10 | 10 / 10 |
| Interfaces (FE, GE ports) | 5x GE RJ45 | 8x GE RJ45 | 10x GE RJ45 | 4x GE RJ45 | 16x GE RJ45 | 20x GE RJ45, 2x Shared Port Pairs (100D only) | 18x GE RJ45, 2x GE SFP | 6x GE RJ45, 4x GE SFP | 10x GE RJ45, 8x GE SFP | 18x GE RJ45, 4x Shared Port Pairs, 2x Bypass Pairs |
| Interfaces (Others) | FWF - a/b/g/n | FWF - a/b/g/n | FWF - a/b/g/n | - | FWF - a/b/g/n | - | - | - | - | - |
| Local Storage | - | - | - | 16 GB | FG/FWF-90D: 32 GB | 32 GB | 64 GB | 120 GB | 120 GB | 60 GB |
| Power Supplies | Single AC Power Supply | Single AC Power Supply | Single AC Power Supply | Single AC Power Supply | Single AC Power Supply | Single AC Power Supply | Single AC Power Supply, opt. Ext RPS | Single AC Power Supply, opt. Ext RPS | Single AC Power Supply, opt. Ext RPS | Single AC Power Supply, opt. Dual PS or Ext RPS |
| Form Factor | Desktop | Desktop | Desktop | Desktop | Desktop | Rack Mount, 1 RU | Rack Mount, 1 RU | Rack Mount, 1 RU | Rack Mount, 1 RU | Rack Mount, 1 RU |
| Variants | WiFi, POE | WiFi, Anal.Modem, Wifi+Ana. Modem, LENC, SFP, POE, ADSL | WiFi, POE, LENC | - | WiFi, POE, LENC, High port density + POE | LENC, High port density, High port density + POE | LENC, POE, High port density, High port density + POE | - | - | DC, LENC |
| | FG-800C | FG-1000C | FG-1240B | FG-1500D | FG-3240C | FG-3600C | FG-3700D | FG-3950B | FG-5001C | FG-5101C |
| Firewall Throughput (1518/512/64 byte UDP) | 20 / 20 / 20 Gbps | 20 / 20 / 20 Gbps | 40-44 / 40-44 / 38-42 Gbps | 80 / 80 / 55 Gbps | 40 / 40 / 40 Gbps | 60 / 60 / 60 Gbps | 160 / 160 / 110 Gbps | 20-120 / 20-120 / 20-120 Gbps | 40 / 40 / 40 Gbps | 40 / 40 / 10 Gbps |
| Firewall Latency | 6 µs | 6 µs | 7 µs | 3 µs | 4 µs | 4 µs | 2 µs | 4 µs | 4 µs | 7 µs |
| Concurrent Sessions | 7 Mil | 7 Mil | 5 Mil | 12 Mil | 10 Mil | 28 Mil | 44 Mil | 20 Mil | 29.5 Mil | 10 Mil |
| New Sessions/Sec | 190,000 | 190,000 | 120,000 | 250,000 | 200,000 | 235,000 | 300,000 | 250K - 300K** | 210,000 | 235,000 |
| Firewall Policies | 10,000 | 100,000 | 100,000 | 100,000 | 100,000 | 100,000 | 100,000 | 100,000 | 100,000 | 100,000 |
| IPSec VPN Throughput | 8 Gbps | 8 Gbps | 16 - 18.5 Gbps | 50 Gbps | 17 Gbps | 25 Gbps | 100 Gbps | 8 - 50.5 Gbps | 17 Gbps | 22 Gbps |
| Max G/W to G/W IPSEC Tunnels | 2,000 | 20,000 | 10,000 | 20,000 | 20,000 | 20,000 | 40,000 | 40,000 | 40,000 | 40,000 |
| Max Client to G/W IPSEC Tunnels | 50,000 | 50,000 | 50,000 | 50,000 | 64,000 | 64,000 | 64,000 | 64,000 | 64,000 | 64,000 |
| SSL VPN Throughput | 1.3 Gbps | 1.3 Gbps | 370 Mbps | 4 Gbps | 3.4 Gbps | 5.3 Gbps | 6 Gbps | 1.2 Gbps | 850 Mbps | 970 Mbps |
| Recommended SSL VPN Users | 10,000 | 10,000 | 1,500 | 10,000 | 30,000 | 30,000 | 30,000 | 25,000 | 30,000 | 25,000 |
| IPS Throughput | 6 Gbps | 6 Gbps | 5 - 8 Gbps | 11 Gbps | 8 Gbps | 14 Gbps | 23 Gbps | 5- 20 Gbps | 9.8 Gbps | 9.4 Gbps |
| Antivirus Throughput (Proxy-Based/ Flow-Based) | 1.7 / 3.1 Gbps | 1.7 / 3.1 Gbps | 1.2 / 1.6 Gbps | 4.3 / 13 Gbps | 2.6 / 9 Gbps | 5.8 / 18 Gbps | 7.5 / 18 Gbps | 4 / 5 - 15 Gbps | 3 / 4 Gbps | 2 / 5 Gbps |
| Max FortiAPs (Total, Tunnel) | 1024 / 512 | 4096 / 1024 | 4096 / 1024 | 4096 / 1024 | 4096 / 1024 | 4096 / 1024 | 4096 / 1024 | 4096 / 1024 | 4096 / 1024 | 4096 / 1024 |
| Max FortiTokens | 1,000 | 5,000 | 5,000 | 5,000 | 5,000 | 5,000 | 5,000 | 5,000 | 5,000 | 5,000 |
| Max Registered Endpoints | 2,000 | 8,000 | 8,000 | 8,000 | 20,000 | 20,000 | 20,000 | 20,000 | 20,000 | 20,000 |
| Virtual Domains (Default/Max) | 10 / 10 | 10 / 250 | 10 / 250 | 10 / 250 | 10 / 500 | 10 / 500 | 10 / 500 | 10 / 500 | 10 / 500 | 10 / 500 |
| Interfaces | 2x 10GE SFP+, 14x GE RJ45, 8x Shared Port Pairs, 2x Bypass Pairs | 2x 10GE SFP+, 14x GE RJ45, 8x Shared Port Pairs, 2x Bypass Pairs | 16x GE RJ45, 24x GE SFP | 8 x 10GE SFP+/GE, 18x GE RJ45, 16x GE SFP | 12x 10GE SFP+, 2x GE RJ45, 16x GE SFP | 12x 10GE SFP+, 2x GE RJ45, 16x GE SFP | 4 x 40GE QSFP+, 20 x 10GE SFP+/GE SFP, 8 x SFP+, 2 x GE RJ45 | 2x 10GE SFP+, 2x GE RJ45, 4x GE SFP | 2x 10GE SFP+, 2x GE RJ45 | 4x 10GE SFP+, 2x GE RJ45 |
| Local Storage | 60 GB | 120 GB | 64 GB (384 GB Max) | 240 GB | 64 GB | 128 GB | 960 GB | 256 GB | 128 GB | 64 GB |
| Power Supplies | Single AC Power Supply, opt. Dual PS or Ext RPS | Dual PS | Dual PS | Dual PS | Dual PS | Dual PS | Dual PS | Dual PS | Chassis Based | Chassis Based |
| Form Factor | Rack Mount, 1 RU | Rack Mount, 2 RU | Rack Mount, 2 RU | Rack Mount, 2 RU | Rack Mount, 2 RU | Rack Mount, 3 RU | Rack Mount, 3 RU | Rack Mount, 3 RU | ATCA Blade | ATCA Blade |
| Variants | DC | DC, LENC | DC | - | DC | DC | - | DC, LENC | - | - |

* Featured Top selling models, for complete FortiGate offerings please visit www.fortinet.com. FortiGate virtual appliances are also available. Specifications based on FortiOS V5.2+

** With FMC-XHD

FortiManager Centralized Management Platform

| | FMG-200D | FMG-300D | FMG-1000D | FMG-4000E | FMG-VM-BASE | FMG-VM-10-UG | FMG-VM-100-UG | FMG-VM-1000-UG | FMG-VM-5000-UG | FMG-VM-U-UG |
|---------------------------------|---------------------|---------------------|---------------------|---------------------|---------------------------|--------------|---------------|---------------------|---------------------|---------------------|
| Max Licensed Devices/ADoms | 30 | 300 | 1,000 | 4,000 | 10 | +10 | +100 | +1,000 | +5,000 | Unlimited |
| Max Web Portals/Users | - | - | 1,000 | 4,000 | 10 | +10 | +100 | +1,000 | +5,000 | Unlimited |
| GB Logs/Day | 2 | 2 | 2 | 10 | 1 | 2 | 5 | 10 | 25 | 50 |
| Locally Hosted Security Content | AV, IPS, VM, WF, AS | AV, IPS, VM, WF, AS | AV, IPS, VM, WF, AS | AV, IPS, VM, WF, AS | AV, IPS, VM | AV, IPS, VM | AV, IPS, VM | AV, IPS, VM, WF, AS | AV, IPS, VM, WF, AS | AV, IPS, VM, WF, AS |
| Total Interfaces | 4x GE RJ45 | 4x GE RJ45 | 6x GE RJ45, 2x SFP | 4x GE RJ45, 2x SFP | 1 / 4 (vNIC Min / Max) | | | | | |
| Storage Capacity | 1x 1 TB | 2x 2TB | 4x 2 TB | 8x 2 TB | 80 GB / 16 TB (Min / Max) | | | | | |

FortiAnalyzer Centralized Logging & Reporting Solution

| | FAZ-200D | FAZ-300D | FAZ-1000D | FAZ-2000B | FAZ-3000E | FAZ-3500E | FAZ-VM-BASE | FAZ-VM-GB1 | FAZ-VM-GB5 | FAZ-VM-GB25 | FAZ-VM-GB100 |
|--------------------------------|------------|----------------|------------------------------------|-----------------------------|------------------------------------|------------------------------------|-------------|------------|------------|-------------|--------------|
| GB Logs/Day | 5 | 15 | 25 | 75 | 250 | Unlimited* | 1 | +1 | +5 | +25 | +100 |
| Sessions/Day | 18 Mil | 55 Mil | 85 Mil | 260 Mil | 850 Mil | Unlimited* | 3.5 Mil | 3.5 Mil | 18 Mil | 85 Mil | 360 Mil |
| Max Log Rate (standalone Mode) | 350 | 625 | 1,000 | 3,000 | 10,000 | Unlimited* | - | - | - | - | - |
| Max. Licensed Devices/ADoms | 150 | 200 | 2,000 | 2,000 | 2,000 | 2,000 | 10,000 | 10,000 | 10,000 | 10,000 | 10,000 |
| Total Interfaces | 4x GE RJ45 | 4x GE RJ45 | 6x GE RJ45, 2x SFP | 6x GE RJ45 | 4x GE RJ45, 2x GE SFP | 2x GE RJ45, 2x GE SFP | - | - | - | - | - |
| Storage Capacity | 1x 1 TB | 2x 2 TB | 4x 2 TB | 2x 2 TB (12 TB Max) | 8x 2 TB (16 TB Max) | 12x 2 TB (48 TB Max) | 200 GB | +200 GB | +1 TB | +8 TB | +16 TB |
| RAID Support | No | Yes (Mirrored) | Yes, (RAID 0, 1, 5, 6, 10, 50, 60) | Yes, (RAID 0, 1, 5, 10, 50) | Yes, (RAID 0, 1, 5, 6, 10, 50, 60) | Yes, (RAID 0, 1, 5, 6, 10, 50, 60) | - | - | - | - | - |

* Only restricted to the hardware platform performance (e.g. there are no software licensing limitations)

FortiAP Wireless Access Point

| | FAP-11C | FAP-14C | FAP-28C | FAP-112B | FAP-221B/223B | FAP-221C | FAP-222B | FAP-320B | FAP-320C |
|---|---------------------|---------------------|---------------------|---------------------|---|--|---|--|---|
| Target Environment | Remote | Remote | Remote | Indoor/Outdoor | Indoor | Indoor | Indoor/Outdoor | Indoor | Indoor |
| Number of Radio / Antennas | 1 / 1 Internal | 1 / 1 Internal | 1 / 2 Internal | 1 / 1 Internal | 221B: 2 / 4 Int. 223B: 2 / 4 Ext. | 2 / 4 Internal | 2 / 4 External | 2 / 6 internal | 2 / 6 internal |
| TX / RX Streams (802.11n / ^802.11ac) | 1x1 MIMO - 150 Mbps | 1x1 MIMO - 150 Mbps | 2x2 MIMO - 300 Mbps | 1x1 MIMO - 150 Mbps | 2x2 MIMO dual spatial stream - 600 Mbps Total | 2x2 MIMO dual spatial stream - 1167 Mbps Total | 2x2 MIMO dual spatial stream - 600 Mbps Total | 3x3 MIMO with 3 spatial streams - 900 Mbps Total | 3x3 MIMO with 3 spatial streams - 1750 Mbps Total |
| Total (Client access + Monitoring) Simultaneous SSIDs | 8 | 8 | 8 | 8 | 16 | 16 | 16 | 16 | 16 |
| Max Transmission Power | 17dBm (50mW) | 17dBm (50mW) | 17dBm (50mW) | 24 dBm (250mW) * | 17dBm (50mW) | 17dBm (50mW) | 27dBm (500mW) hardware capable | 24 dBm (250mW) * | 24 dBm (250mW) * |
| Ethernet Interface | 2x GE RJ45 | 5x FE | 10x GE RJ45 | 2x FE | 1x GE RJ45 | 1x GE RJ45 | 1x GE RJ45 | 2x GE RJ45 | 2x GE RJ45 |
| Power over Ethernet (PoE) | - | - | - | 802.3af | 802.3af | 802.3af | 802.3at | 802.3af / 802.3at | 802.3af / 802.3at |

* Frequency selection and power may be restricted to abide by regional regulatory compliance laws.

FortiSwitch Secured Access Switch

| | FSW-28C | FSW-108D-POE | FSW-224D-POE | FSW-324B-POE | FSW-348B | FSW-448B |
|-------------------------------------|----------------------------------|--|---|--|----------------------------------|--------------------------|
| Total Interfaces | 8 x GE RJ45 LAN, 2 x GE RJ45 WAN | 8x GE POE RJ45 ports, 2x Shared Port Pairs | 20x GE RJ45 ports (incl. 12 PoE), 4x GE Shared Port Pairs | 16x GE PoE, 4x GE PoE+, 4x Shared Port Pairs | 48 GE RJ45, 2x Shared Port Pairs | 48 GE RJ45, 2x 10GE SFP+ |
| Switch Capability | 16 Gbps | 20 Gbps | 48 Gbps | 48 Gbps | 96 Gbps | 136 Gbps |
| FortiGate Switch Controller Support | Yes (Remote) | Yes | Yes | Yes | Yes | Yes |

For Complete selection of FortiSwitches, please refer to <http://www.fortinet.com/products/fortiswitch>

FortiAuthenticator User Identity Management Server

| | FAC-200D | FAC-400C | FAC-1000D | FAC-3000D | FAC-VM Base | FAC-VM-100-UG | FAC-VM-1000-UG | FAC-VM-10000-UG | FAC-VM-100000-UG |
|------------------------------------|----------------|--------------------|-------------------------|-------------------------|----------------|-------------------|------------------------|----------------------------|-------------------------------|
| Max Local/Remote Users/ User Group | 500 / 500 / 25 | 2,000 / 2,000 / 50 | 10,000 / 10,000 / 2,000 | 40,000 / 40,000 / 4,000 | 100 / 100 / 10 | +100 / +100 / +10 | +1,000 / +1,000 / +100 | +10,000 / +10,000 / +1,000 | +100,000 / +100,000 / +10,000 |
| Max FortiToken | 500 | 2,000 | 10,000 | 40,000 | 200 | +200 | +2,000 | +20,000 | +200,000 |
| Max NAS Devices | 50 | 200 | 1,000 | 4,000 | 10 | +10 | +100 | +1,000 | +10,000 |

FortiSandbox Advanced Threat Prevention System

| | FSA-1000D | FSA-3000D |
|----------------------------|-----------|-----------|
| VM Sandboxing (Files/Hour) | 160 | 560 |
| AV Scanning (Files/Hour) | 6,000 | 15,000 |
| Number of VMs | 8 | 28 |

FortiDDOS Hardware Accelerated DDoS Mitigator

| | FDD-400B | FDD-800B | FDD-1000B | FDD-2000B |
|--------------------------|-----------|-----------|-----------|-----------|
| Throughput (Full Duplex) | 4 Gbps | 8 Gbps | 12 Gbps | 24 Gbps |
| Simultaneous Connections | 1 Mil | 2 Mil | 3 Mil | 4 Mil |
| Session Setup/Tear-down | 100 K/Sec | 200 K/Sec | 300 K/Sec | 600 K/Sec |

FortiMail Messaging Security Server

| | FML-200D | FML-400C | FML-1000D | FML-3000D | FML-VM00 | FML-VM01 | FML-VM02 | FML-VM04 | FML-VM08 |
|-----------------------------|----------|----------|-----------|------------------------|----------|--------------|--------------|--------------|--------------|
| Email Routing* (Msg/Hr) | 76,000 | 150,000 | 680,000 | 1.5 Mil | 3,600 | 34,000 | 67,000 | 306,000 | 675,000 |
| Performance AS+AV* (Msg/Hr) | 58,000 | 120,000 | 500,000 | 1.3 Mil | 2,700 | 26,000 | 52,000 | 225,000 | 585,000 |
| Email Domains | 20 | 100 | 800 | 2,000 | 2 | 20 | 100 | 800 | 2,000 |
| Server Mode Mailboxes | 150 | 400 | 1,500 | 3,000 | 50 | 150 | 400 | 1,500 | 3,000 |
| Storage Capacity | 1x 1 TB | 2x 1 TB | 2x 2 TB | 2x 2 TB (12 TB Max) | 1x 146GB | 50 GB - 1 TB | 50 GB - 2 TB | 50 GB - 4 TB | 50 GB - 8 TB |

* Measured based on 100KB message size, no queuing.

FortiWeb Web Application Firewall

| | FWB-400C | FWB-1000D | FWB-3000D/Fsx | FWB-4000D | FWB-VM01/-VM02/- VM04/-VM08 |
|-------------------|------------|---|---|---|---------------------------------------|
| Throughput (HTTP) | 100 Mbps | 750 Mbps | 1.5 Gbps | 4 Gbps | 25 Mbps /100 Mbps/ 500 Mbps 1 Gbps |
| Total Interfaces | 4x GE RJ45 | 2x GE RJ45, 4x GE RJ45 Bypass, 2x GE SFP | 6x GE RJ45, 2x GE Bypass /Fsx: 6x GE RJ45 , 2x 10GE SFP+ Bypass | 6x GE RJ45, 2x GE RJ45 Bypass, 2x GE SX Bypass, 2x 10GE SFP+ Bypass | - |

FortiADC Application Delivery Controller

| | FAD-200D | FAD-300E | FAD-400E | FAD-600E | FAD-1000E | FAD-1500D | FAD-2000D | FAD-4000D | FAD-VM01/VM02/VM04/VM08 |
|-------------------|------------|------------|------------|------------------------|------------------------|------------------------|-------------------------|-------------------------|-------------------------|
| Throughput (HTTP) | 2.7 Gbps | 4.8 Gbps | 8 Gbps | 12 Gbps | 15 Gbps | 20 Gbps | 30 Gbps | 50 Gbps | |
| Total Interfaces | 4x GE RJ45 | 6x GE RJ45 | 8x GE RJ45 | 2x 10GE, 8x GE RJ45 | 2x 10GE, 8x GE RJ45 | 4x 10GE, 8x GE RJ45 | 4x 10GE, 16x GE RJ45 | 8x 10GE, 16x GE RJ45 | Hardware Dependent |

Virtual Appliance Support Matrix

| | VMWare vSphere v4.0/4.1 | VMWare vSphere v5.0/5.1/5.5 | Citrix Xen Server v5.6 SP2 | Citrix Xen Server v6.0 | Xen | KVM | Amazon AWS | Microsoft Hyper-V 2008 R2 | Microsoft Hyper-V 2012 |
|-----------------------|-------------------------------|-----------------------------------|----------------------------------|------------------------------|-----|-----|---------------|---------------------------------|------------------------------|
| FortiGate-VM | • | • | • | • | • | • | • | • | • |
| FortiManager-VM | • | • | | | | | • | • | • |
| FortiAnalyzer-VM | • | • | | | | | • | • | • |
| FortiWeb-VM | • | • | | • | • | | • | | • |
| FortiMail-VM | • | • | | | | | | | |
| FortiAuthenticator-VM | • | • | | | | | | | |
| FortiADC-VM | | • | | | | | | | |
| FortiCache-VM | • | • | | | | | | | |
| FortiVoice-VM | | • | | | | | | | |
| FortiRecorder-VM | | • | | | | | | | |

Also Available

AscenLink Link Load Balancer

FortiBridge Failopen Appliance

FortiCache Secure Web Cache

FortiCamera NetworkVideo Security Solution

FortiClient Host Security Client

FortiDB Database Security System

FortiDNS Secure DNS Cache

FortiExtender 3G/4G WAN Extender

FortiToken 2 Factor Authentication Token

FortiVoice Secure VoIP Solution

This document is provided as a convenient comparison of Fortinet products and services. The datasheet for any product or service can be found on www.fortinet.com should be consulted for the most updated specifications.

Copyright© 2014 Fortinet, Inc. All rights reserved. Fortinet®, FortiGate®, FortiCare® and FortiGuard®, and certain other marks are registered trademarks of Fortinet, Inc., and other Fortinet names herein may also be registered and/or common law trademarks of Fortinet. All other product or company names may be trademarks of their respective owners. Performance and other metrics contained herein were attained in internal lab tests under ideal conditions, and actual performance and other results may vary. Network variables, different network environments and other conditions may affect performance results. Nothing herein represents any binding commitment by Fortinet, and Fortinet disclaims all warranties, whether express or implied, except to the extent Fortinet enters a binding written contract, signed by Fortinet's General Counsel, with a purchaser that expressly warrants that the identified product will perform according to certain expressly-identified performance metrics and, in such event, only the specific performance metrics expressly identified in such binding written contract shall be binding on Fortinet. For absolute clarity, any such warranty will be limited to performance in the same ideal conditions as in Fortinet's internal lab tests. Fortinet disclaims in full any covenants, representations, and guarantees pursuant hereto, whether express or implied. Fortinet reserves the right to change, modify, transfer, or otherwise revise this publication without notice, and the most current version of the publication shall be applicable.

PROMTX-2014-R30-SEP